

Features

- Records show: 80% purchase is for neonates and children
- 3.5 inch auto rotation TFT display for SpO₂, PI, Plethysmogram, PR and Temperature
- Creative Patented MoveOxy[™]SpO₂ technology with artifact removal and anti-motion performance
- Various choice of SpO2 probe for Adult, Pediatric and Neonate particularly
- Inbuilt lithium battery up to 20 hours continuous monitoring
- · Adjustable alarm limit, pitch tone level, key tone and brightness
- Up to 1000 hours SpO2 data storage
- Upgradeable to infrared ear temperature



Technical Specifications

SpO₂

Technique: Dual-wavelength LED Measuring range: 35%~100%

Measuring accuracy: ±3% (range from 70% to 100%)

Pulse Rate

Measuring range: 30bpm~250bpm Measuring accuracy: ±2bpm or ±2%

Temperature(Option)

Measuring range: 32 °C ~ 43 °C Measuring accuracy: ±0.2 °C Measuring time: < 5 seconds Measuring probe: Infrared ear probe

Measuring Mode

Continuous or Spot check mode

Perfusion Index

PI Range: 0.2%~20%

Data Storage

Up to 1000 hours

Display

3.5 TFT display

Power Supply

Lithium battery

Charging

Charging stand or USB cable

Dimension

158.3mm x 73.2mm x 25.0mm

Net Weight

240g

Data Upload

USB cable or wireless

Operating Environment

Operating Temperature: 5°C ~40°C Operating Humidity: 30%~80%



Adult Clip Sensor



Pediatric Soft Sensor



Adult Soft Sensor



Multiple-use Y sensor





Neonate/Infant wrap sensor





Shenzhen Creative Industry Co., Ltd.

2/F, Block 3, Nanyou Tian'an Industry Town, Shenzhen, GD, 518054 P.R. China Tel:+86 755 26433514 Fax: +86 755 26430930 www.creative-sz.com info@creative-sz.com